AFOSR TR 96

ICAM

FINAL TECHNICAL REPORT

on

GRAPHICAL PRE-AND POST-PROCESSING
FOR SCIENTIFIC COMPUTING
AN AFOSR - DOD DURIP EQUIPMENT GRANT

AFOSR GRANT F49620-94-1-0457 for the period 30 September 1994 - 29 September 1995

ICAM REPORT 96-02-01

INTERDISCIPLINARY CENTER FOR APPLIED MATHEMATICS



VIRGINIA POLYTECHNIC INSTITUTE AND STATE UNIVERSITY

DIIC QUALITY INCLESTED L

Approved to public more

Distribution Unlimited

Blacksburg, Virginia 24061-0531

FINAL TECHNICAL REPORT

on

GRAPHICAL PRE-AND POST-PROCESSING FOR SCIENTIFIC COMPUTING AN AFOSR - DOD DURIP EQUIPMENT GRANT

AFOSR GRANT F49620-94-1-0457 for the period 30 September 1994 - 29 September 1995


ICAM REPORT 96-02-01

A THEMSTRUE HOSTIDENTERS

Apperved he public related Distribution Unitediad

19960801 101

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF COLOR PAGES WHICH DO NOT REPRODUCE LEGIBLY ON BLACK AND WHITE MICROFICHE.

FINAL TECHNICAL REPORT

ON

GRAPHICAL PRE-AND POST-PROCESSING FOR SCIENTIFIC COMPUTING AN AFOSR - DOD DURIP EQUIPMENT GRANT

AFOSR GRANT F49620-94-1-0457

for the period

30 September 1994 - 29 September 1995

by

John A. Burns, Director
Air Force Center for Optimal Design And Control

Interdisciplinary Center for Applied Mathematics
Wright House / West Campus Drive
Virginia Polytechnic Institute & State University
Blacksburg, Virginia 24061-0531

February 11, 1996

Prepared for the: Air Force Office of Scientific Research

Mathematical and Computer Sciences - NM

110 Duncan Avenue, Suite B115 Bolling AFB, DC 20332-0001

REPORT DOCUMENTATION PAGE			OMB No. 0704-0188
Public reporting burden for this collection of in	formation is estimated to average 1 hour per re	esponse, including the time for rev formation. Send comments regard quarters Services, Directorate for udget, Paperwork Reduction Proje	viewing instructions, searching existing data sources, ding this burden esting de or any other aspect of this information Operations and Reports, 1215 Lefferson oct (0704-0188), Washington, DC 20503.
1. AGENCY USE ONLY (Leave blan	1k) 2. REPORT DATE	3. REPORT TYPE AND	DATES COVERED
	2/11/96	Final Report	, 9/30/94 - 9/29/95 5. FUNDING NUMBERS
4. TITLE AND SUBTITLE			
Graphical Pre-and Post-proces	ssing for Scientific Computing		(5) 740500 044 0457
6. AUTHOR(S)		,	(G) F49620-94-1-0457
J.A. Burns, E.M. Cliff and M.			ORCANIZATION
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)			8. PERFORMING ORGANIZATION REPORT NUMBER
Intendiquialinam Canton for A	nnlied Mathematics		
Interdisciplinary Center for Applied Mathematics Wright House, West Campus Drive			
Virginia Polytechnic Institute and State University			ICAM Report 96-02-01
Blacksburg, Virginia 24061-0531 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING / MONITORING
3. St Ordoning / Morning / Section 1			AGENCY REPORT NUMBER
	Danasak		
Air Force Office of Scientific Research Code NM			
Bolling AFB, DC 20332			
11. SUPPLEMENTARY NOTES			
			(a) Distribution coof
12a. DISTRIBUTION/AVAILABILITY STATEMENT			12b. DISTRIBUTION CODE
Unlimited			
42 ARCTRACT (44 - 1 - 200	del		
13. ABSTRACT (Maximum 200 work	US)		
m	ntains a summary of the equipm	ent nurchased and the	research conducted under the
AFOSR DURIP Grant F4962	0-94-J-0457, titled "Graphical Pr	e-and Post-processing for	or Scientific Computing", for
AFOSR DURIP Grant F49620-94-J-0457, titled "Graphical Pre-and Post-processing for Scientific Computing", for the period 30 September 1994 to 30 September 1995. During this period, the equipment was used to expand the			
campbilities of CODAC researchers to develop visualization tools that enhance scientific understanding and			
facilitate engineering design. Much of the work is concentrated on optimal design and control of systems described by partial differential equations. Therefore, the graphical tools were needed to develop spatial			
discretizations and associated computational grids. The sensitivity equation method is being applied to various			
shape optimization and flow tailoring problems. The computational and graphical equipment purchased under this			
grant is being used to develop an interactive design tools for aerospace systems. The report contains a description of the equipment and a brief summary of some of the on-going research projects that are using this equipment.			
of the equipment and a brief s	summary of some of the on-going	g research projects that	are using this equipment.
	,		
14. SUBJECT TERMS	15. NUMBER OF PAGES		
Optimal Design and Control of Fluids, Scientific Computation, Visualization			16. PRICE CODE
Optimal Design and Control	or runus, scientific Computation		
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFI OF ABSTRACT	CATION 20. LIMITATION OF ABSTRA
Unclassified	Unclassified	Unclassified	UL

1 Equipment Purchased

The principal equipment purchased under the grant were

- 1. four SGI Indigo workstations
- 2. two HP 1600CM color printers

2 Scientific Justification

The equipment purchased under this grant has enhanced our abilities to do fundamental research and has aided in the industrial transition of this work in at least three ways:

- 1. pre-processing for scientific computations
- 2. post-processing for scientific visualization
- 3. development of interactive design tools

2.1 Pre-processing for scientific computations

Much of our work is focused on control and design of systems described by partial differential equations. Accordingly, there is a need for spatial discretization and associated computational grids. Furthermore, the geometrical complexity of three-dimensional objects encountered in realistic scientific computations requires substantial preparation of grids before one can enter into the solution phase of a numerical simulation. For example, in [1], we studied optimization of the shape of a forebody simulator (see, [3],[8]), using a flow solver based on unstructured grids [2]. Unstructured grids are important in applications, wherein actual boundaries may be irregular.

The computational geometry for the problem is described by a trapezoidal domain with the forebody removed. A typical grid is shown in 1. The boundary conditions are specified in the following way: 1) inflow conditions are applied on the left side and slanted top portion, 2) a simple first order extrapolation outflow is specified for the right side, 3) tangency is applied on the curved forebody, and 4) a symmetry condition is applied on the horizontal boundary preceding the forebody. Modern engineering workstations, such as the SGI Indigo's obtained under this grant, are essential to the efficient

generation of such grids. The ability to display and manipulate these grids is crucial to the timely solution of such flow optimization problems.

2.2 Post-processing for scientific visualization

Simulation of the response of distributed systems commonly produces two and/or three-dimensional time-dependent data. Scientific visualization is an emerging discipline that provides tools for representing these responses in ways that help the analyst understand and interpret the results. In [9] we study optimal LQG control of a driven cavity. In this problem the goal is to compute optimal feedback functional gains and and use the spatial information in these gains to place sensors/actuators for feedback control. It is important to display these functional gains to the analyst so that he can use the visual information to guide the sensor placement, for example. With the feedback controller in hand, one is interested in simulating the response to demonstrate the effectiveness of the control algorithm. In this facet it is useful to generate time varying flows in the cavity, driven by disturbances. The results of these similation can be animated for presentation on our work-stations.

2.3 Development of interactive design tools

Advances in computational arts - analysis, software and hardware - have greatly enhanced the process of analyzing proposed design concepts. Such advances have occured in virtually all engineering disciplines but especially in those related to advanced aerospace systems. While such analysis tools are important, an even bigger payoff awaits the development of advanced tools for design synthesis.

We expect that before formal optimization is adopted as a common tool, it will be useful to produce tools that guide the contemporary designer. For example, in addition to displaying the simulated flow for a current design, one might also provide information about how a specific geometric change will alter the flow. The designer would use this information, along with a notion of his 'goal' to adjust the geometry and simulate a new flow. We have developed numerical procedures for the efficient calculation of certain design sensitivities (see, [4], [5], [6]) for high-speed flow problems. In [1] we applied these ideas to a chemically reacting flow problem with five species of air [7], [10] [11]. Shown in 2 is the computed sensitivity for the amount of nitrous

oxide in the flow to the inflow velocity. From such information, the designer can judge the effect of such changes on the flow.

3 Educational Component

The Interdisciplinary Center for Applied Mathematics (ICAM) was formed in August 1987 to to promote and facilitate interdisciplinary research and education in applied mathematics at Virginia Polytechnic Institute and State University. The goal of ICAM is to enhance the historical links among mathematics, engineering and the sciences. Core participants in ICAM are committed to providing interdisciplinary research experience for both graduate and undergraduate students. The equipment purchased under this grant is available for use by qualified students in their research and in their formal studies.

References

- [1] Appel, J.R., Godfrey, A. Cliff, E.M. and Gunzburger, M.D., "Optimization-based design in high-speed flows", in *CFD for Design and Optimization*, O Baysal, ed pp 61-68, Presented at ASME International Mechanical Engineering Congress and Exposition, San Francisco, CA, Nov. 1995.
- [2] Applebaum, M.P. and Walters, R.W., UCFD, An Unstructured Computational Fluid Dynamics Package, Virginia Tech, Blacksburg, VA, 1995.
- [3] Beale, D.K. and Collier, M.S., "Validation of a free-jet technique for evaluating inlet-engine compatibility," AIAA PAPER 89-2325, Presented at 25th AIAA, ASME, SAE and ASEE Joint Propulsion Conference, Monterey, CA, 1989.
- [4] Borggaard, J.T., Burns, J.A., Cliff, E.M. and Gunzburger, M.D., "Sensitivity calculations for a 2D, inviscid, supersonic forebody problem", Identification and Control of Systems Governed by Partial Differential Equations, H.T. Banks et al., ed., SIAM Publications, Philadelphia, PA, 1993.

- [5] Borggaard, J.T., "The Sensitivity Equation Method for Optimal Design", Ph.D. Dissertation, Department of Mathematics, VPI & SU, Blacksburg, VA, Dec. 1994
- [6] Borggaard, J.T., Burkardt, J.V., Gunzburger, M.D. and Peterson, J.L., Eds., 1995, Optimal Design and Control, Birkhauser, Boston, MA.
- [7] Grossman, B. and Cinnella, P., "Flux-split algorithms for flows with non-equilibrium chemistry and vibrational relaxation", J. Computational Physics, Vol. 88, pp 131-168, 1990.
- [8] Huddleston, D., "Development of a free-jet forebody simulator design optimization method", *Tech. Rept. AEDC-TR-90-22*, Arnold Engineering Development Center, Arnold AFB, TN, 1990.
- [9] King, B.B. and Ou, Y.R., "Nonlinear dynamic compensator design for flow control in a driven cavity", Proceedings of the IEEE Conference on Decision and Control, New Orleans, LA, pp 3741 - 3746, Dec. 1995.
- [10] McGrory, W., Slack, D.C., Applebaum, M.P. and Walters, R.W., GASP: The General Aerodynamic Simulation Package, Version 2.2, User's Guide, AeroSoft Inc., Blacksburg, VA, 1993.
- [11] Walters, R.W., Cinnella, P., Slack, D.C. and Halt, D., "Characteristic-based algorithms for flows in thermo-chemical nonequilibrium", AIAA J., Vol. 30, No. 5, pp 1304-1313, 1992.




Figure 1: Typical flow and mesh for the forebody simulator on an unstructured mesh.

NO Mass Fraction Sensitivity to Free-Stream Velocity




Figure 2: Sensitivity of NO fraction